

WV-CW1026 Full HD Compatible 2 Megapixel Outdoor IR Network Dome Camera

Appearance



Main Specification

Image Sensor	1/2.8" 2MP CMOS
Lens	F2.8 , Fixed Iris
Angular Field of View	115° (H), 62° (V)
Min. Illumination	Color:0.01 lx @(F1.2, AGC ON), 0.028 lx @(F2.0, AGC ON) B/W:0.001 lx @(F1.2, AGC ON), 0.0028 lx @(F2.0, AGC ON), 0 lx (IR LED On)
Dynamic Range	Digital WDR
Electronic Shutter Speed	Auto
Day and Night	TDN
IR Distance	Max. 20m(15ea)
Video Compression	H.265, 264(MP), H.265+, H.264+
Resolution	1920×1080(1080p), 1280×720(720p), 704×480(D1), 640×480, 352×240, 320×240
Bitrate Control	32 Kbps~8Mbps
Max. Frame Rate	30fps @ 1920×1080 + 30fps @ 4CIF
Multistreaming	2 (Main Stream, Sub Stream)
Audio Compression	G.711, G.722.1, G.726, MP2L2, PCM
Video Outputs	-
Audio Inputs/Outputs	Inputs:1 (line in) Outputs:1 (line out), mono sound
Alarm Inputs	×1
Alarm Outputs	×1
Ethernet	×1, RJ45 10 / 100M Self-adaptive Ethernet Port
ONVIF	ONVIF (PROFILE S, PROFILE G)
Connector	Network Port:RJ-45 Alarm In/Out:Cable Audio In/Out: Cable
Dimensions	Approx. 111(φ) ×82.4(D) mm
Weight	Approx. 400g
Operating Temperature	-30~+60°C / Humidity:RH95% Max
Power Source	PoE: (802.3af, 36~57V), 0.2~0.1A, Max. 6.5W
Power Consumption	12VDC, 0.4A, Max. 5W
IP Grade	IP67
Supported memory card	Support built-in micro SD/SDHC/SDXC Card(128GB) Local Storage and NAS (NFS,SMB/CIFS)